



SKYパッキン

SKYパッキン寸法表

単位：mm

呼 び 番 号		パッキン及びみぞ寸法							併用バックアップリング (PT111)
標準 (RN 906)	耐熱用(RF 905)(RF 907)	d	D	H	G _A	G _B	D ₁	d ₁ (参考)	
SKY- 60	SKY- 60F	60	70	6	7	8.5	69	60.6	TCS- 70 × 60
SKY- 60A	SKY- 60AF	60	71	7	8	9.5	70	60.6	TCS- 71 × 60
SKY- 61 71 6		61	71	6	7	8.5	70	61.6	
SKY- 63	SKY- 63F	63	73	6	7	8.5	72	63.6	TCS- 73 × 63
SKY- 65	SKY- 65F	65	75	6	7	8.5	74	65.6	TCS- 75 × 65
SKY- 67	SKY- 67F	67	77	6	7	8.5	76	67.6	TCS- 77 × 67
SKY- 70	SKY- 70F	70	80	6	7	8.5	79	70.6	TCS- 80 × 70
SKY- 71	SKY- 71F	71	80	6	7	8.5	79	71.6	TCS- 80 × 71
SKY- 75	SKY- 75F	75	85	6	7	8.5	84	75.6	TCS- 85 × 75
SKY- 80	SKY- 80F	80	90	6	7	8.5	89	80.6	TCS- 90 × 80
SKY- 85 95 6		85	95	6	7	8.5	94	85.6	TBC- 95 × 85
SKY- 85	SKY- 85F	85	100	9	10	12	98	85.6	TCS- 100 × 85
SKY- 86	SKY- 86F	86	100	8.5	9.5	11.5	98	86.6	TCS- 100 × 86
SKY- 90 100 6		90	100	6	7	8.5	99	90.6	
SKY- 90	SKY- 90F	90	105	9	10	12	103	90.6	TCS- 105 × 90
SKY- 95	SKY- 95F	95	110	9	10	12	108	95.6	TCS- 110 × 95
SKY- 96 111 9		96	111	9	10	12	109	96.6	
SKY- 98	SKY- 98F	98	112	8.5	9.5	11.5	110	98.6	TCS- 112 × 98
SKY- 100	SKY- 100F	100	115	9	10	12	113	100.6	TCS- 115 × 100
SKY- 105 120 9		105	120	9	10	12	118	105.6	TBC- 120 × 105
SKY- 106	SKY- 106F	106	120	8.5	9.5	11.5	118	106.6	TCS- 120 × 106
SKY- 110 125 9		110	125	9	10	12	123	110.6	TBC- 125 × 110
SKY- 112	SKY- 112F	112	125	8.5	9.5	11.5	123	112.6	TCS- 125 × 112
SKY- 112A	SKY- 112AF	112	125	9	10	12	123	112.6	TCS- 125 × 112
SKY- 115 130 8.5		115	130	8.5	9.5	11.5	128	115.6	TBC- 130 × 115
SKY- 118	SKY- 118F	118	132	8.5	9.5	11.5	130	118.6	TCS- 132 × 118
SKY- 119 133 8.5		119	133	8.5	9.5	11.5	131	119.6	
SKY- 120 135 9		120	135	9	10	12	133	120.6	TBC- 135 × 120
SKY- 125	SKY- 125F	125	140	9	10	12	138	125.6	TCS- 140 × 125
SKY- 130 145 9		130	145	9	10	12	143	130.6	TBC- 145 × 130
SKY- 132	SKY- 132F	132	145	8.5	9.5	11.5	143	132.6	TCS- 145 × 132
SKY- 136	SKY- 136F	136	150	8.5	9.5	11.5	148	136.6	TCS- 150 × 136
SKY- 140	SKY- 140F	140	155	9	10	12	153	140.6	TCS- 155 × 140
SKY- 145	SKY- 145F	145	160	9	10	12	158	145.6	TCS- 160 × 145
SKY- 150	SKY- 150F	150	165	9	10	12	163	150.6	TCS- 165 × 150
SKY- 155	SKY- 155F	155	170	9	10	12	168	155.6	TCS- 170 × 155
SKY- 160	SKY- 160F	160	175	9	10	12	173	160.6	TCS- 175 × 160
SKY- 165	SKY- 165F	165	180	9	10	12	178	165.6	TCS- 180 × 165
SKY- 170 185 9		170	185	9	10	12	183	170.6	TBC- 185 × 170
SKY- 175	SKY- 175F	175	190	9	10	12	188	175.6	TCS- 190 × 175
SKY- 180	SKY- 180F	180	200	12	13	15.5	198	180.8	TCS- 200 × 180
SKY- 185 205 12		185	205	12	13	15.5	203	185.8	TBC- 205 × 185
SKY- 190 210 12	SKY- 190 210 12F	190	210	12	13	15.5	208	190.8	
SKY- 195 215 12		195	215	12	13	15.5	213	195.8	
SKY- 200	SKY- 200F	200	220	12	13	15.5	218	200.8	TCS- 220 × 200
SKY- 204	SKY- 204F	204	224	12	13	15.5	222	204.8	TCS- 224 × 204
SKY- 205 225 12		205	225	12	13	15.5	223	205.8	
SKY- 210 230 12	SKY- 210 230 12F	210	230	12	13	15.5	228	210.8	TBC- 230 × 210
SKY- 215 235 12		215	235	12	13	15.5	233	215.8	TBC- 235 × 215

★ご注文・お問合せは、呼び番号にてご指示下さい。
★表中・呼び番号が色地のものは在庫しております。

★SKY-18未満は分割みぞにしてください。
★SKY-300F以上の耐熱用材質はRF907になります。

